SCTE | STANDARDS

Network Operations Subcommittee

AMERICAN NATIONAL STANDARD

ANSI/SCTE 38-7 2017 (R2022)

Hybrid Fiber/Coax Outside Plant Status Monitoring SCTE-HMS-Transponder Interface Bus (TIB)-MIB Management Information Base (MIB) Definition

NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards and Operational Practices (hereafter called "documents") are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interoperability, interchangeability, best practices, and the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the documents. Such adopting party assumes all risks associated with adoption of these documents and accepts full responsibility for any damage and/or claims arising from the adoption of such documents.

NOTE: The user's attention is called to the possibility that compliance with this document may require the use of an invention covered by patent rights. By publication of this document, no position is taken with respect to the validity of any such claim(s) or of any patent rights in connection therewith. If a patent holder has filed a statement of willingness to grant a license under these rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such a license, then details may be obtained from the standards developer. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this document have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at https://scte.org.

All Rights Reserved
© 2022 Society of Cable Telecommunications Engineers, Inc.
140 Philips Road
Exton, PA 19341

	Document Types and Tags	
Document Type: Specification		
Document Tags:		
☐ Test or Measurement	☐ Checklist	☐ Facility
☐ Architecture or Framework	☐ Metric	
\square Procedure, Process or Method	☐ Cloud	☐ Customer Premises

Document Release History

Release	Date
SCTE 38-7 2002	02/22/2002
SCTE 38-7 2008	12/12/2008
SCTE 38-7 2017	12/04/2017
SCTE 38-7 2017 (R2022)	August 2022

Note: Standards that are released multiple times in the same year use: a, b, c, etc. to indicate normative balloted updates and/or r1, r2, r3, etc. to indicate editorial changes to a released document after the year.

Note: This document is a reaffirmation of SCTE 38-7 2017. No substantive changes have been made to this document. Information components may have been updated such as the title page, NOTICE text, headers, and footers

Contents

1.	SCOPE	5
2.	COPYRIGHT	5
3.	NORMATIVE REFERENCE	5
4.	INFORMATIVE REFERENCE	5
5.	TERMS AND DEFINITIONS	5
6.	REQUIREMENTS	5

1. Scope

This document is identical to SCTE 38-7 2008 except for informative components which may have been updated such as the title page, NOTICE text, headers and footers. No normative changes have been made to this document.

This document contains information about the communications state of devices connected to the transponder, as well as indicating what device-specific MIB each device supports. These devices are typically connected to the transponder via a serial communications link (bus).

2. Copyright

The MIB definition found in this document may be incorporated directly in products without further permission from the copyright owner, SCTE.

3. Normative Reference

ANSI/SCTE 25-3 2005	Hybrid Fiber Coax Outside Plant Status Monitoring – Power Supply to Transponder Interface Bus (PSTIB) Specification v1.1
ANSI/SCTE 36 2007 (formerly HMS 028)	SCTE-ROOT Management Information Base (MIB) Definitions
ANSI/SCTE 37 2008 (formerly HMS 072)	Hybrid Fiber/Coax Outside Plant Status Monitoring SCTE-HMS-ROOTS Management Information Base (MIB) Definition
ANSI/SCTE 38-1 2004 (formerly HMS 026)	Hybrid Fiber/Coax Outside Plant Status Monitoring SCTE-HMS-PROPERTY-MIB Management Information Base (MIB) Definition
ANSI/SCTE 38-3 2008 (formerly HMS 024)	Hybrid Fiber/Coax Outside Plant Status Monitoring SCTE-HMS-COMMON-MIB Management Information Base (MIB) Definition
IETF RFC 1155	Structure and Identification of Management Information for TCP/IP-based Internets [RFC1155-SMI]
IETF RFC 1157	A Simple Network Management Protocol (SNMP) [RFC1157-SNMP]
IETF RFC 1212	Concise MIB Definitions for SNMPv1
IETF RFC 1213	MIB for Network Management of TCP/IP-based internets: MIB-II [RFC1213-MIB] for SNMPv1
IETF RFC 1215	A Convention for Defining Traps for use with the SNMP for SNMPv1

4. Informative Reference

None

5. Terms and Definitions

This document defines the following terms:

Management Information Base (MIB) - the specification of information in a manner that allows standard access through a network management protocol.

6. Requirements

This section defines the mandatory syntax of the SCTE-HMS-TIB-MIB MIB. It follows the IETF Simple Network Management Protocol (SNMP) for defining the managed objects.

The syntax is given below.

```
-- * Module Name: HMS050R5.MIB (SCTE 38-7)
-- * SCTE Status: ADOPTED JANUARY 11, 2002
-- * This MIB contains information about the communications state of
-- * devices connected to the transponder, as well as indicating what
-- * device-specific MIB each device supports. These devices are typically
-- * connected to the transponder via a serial communications link (bus).
__ ****************************
SCTE-HMS-TIB-MIB DEFINITIONS ::= BEGIN
IMPORTS
  OBJECT-TYPE
    FROM RFC-1212
  transponderInterfaceBusIdent
    FROM SCTE-HMS-ROOTS
tibAttachedDevices OBJECT-TYPE
  SYNTAX INTEGER
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
     "Bit Map that indicates addresses of attached devices. Bit set means a device using that address
     is attached to NE.
     Bits Addresses
           Not used
      0
      1
           1
      2
           2
      3
           3
      4
           4
      5
           5
      6
           6
      7
           7
      8
           8
      9
           9
      10
           10
      11
           11
           12
      12
      13
           13
      14
           14
      15
           15
      16
           16
      17
           17
      18
           18
      19
           19
      20
           20
      21
           21
      22
           22
      23
           23
      24
           24
      25
           25
```

STATUS mandatory

```
26
             26
       27
             27
       28
             28
       29
             29
       30
             30
       31
             31
  ::= { transponderInterfaceBusIdent 1 }
tibCommStatus OBJECT-TYPE
  SYNTAX INTEGER
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
     "Bit Map that indicates attached devices that are not communicating. Bit set means a device using that address
      is not communicating. This only applies to addresses whose bit is set in tibAttachedDevices.
      Bits Addresses
             Not used
       1
       2
             2
       3
             3
       4
             4
       5
             5
       6
       8
       9
       10
             10
       11
             11
       12
             12
       13
             13
       14
             14
       15
             15
       16
             16
       17
             17
       18
             18
       19
             19
       20
             20
       21
             21
       22
             22
       23
             23
       24
             24
       25
             25
       26
             26
       27
             27
       28
             28
       29
             29
       30
             30
       31
             31
  ::= { transponderInterfaceBusIdent 2 }
tibDevicesAddressedTable OBJECT-TYPE
  SYNTAX SEQUENCE OF TibDevicesAddressedEntry
  ACCESS not-accessible
```

```
DESCRIPTION
     "Table containing identity of devices addressed by this NE.
     This table should contain entries ONLY for devices that are physically
     connected to the NE. If a device is not connected, no entry should be
     created in the table for that address/index."
  ::= { transponderInterfaceBusIdent 3 }
tibDevicesAddressedEntry OBJECT-TYPE
  SYNTAX TibDevicesAddressedEntry
  ACCESS not-accessible
  STATUS mandatory
  DESCRIPTION
       "Entry containing information about individual devices"
  INDEX { tibDeviceAddress }
  ::= { tibDevicesAddressedTable 1 }
TibDevicesAddressedEntry ::=
  SEQUENCE
     tibDeviceAddress
        INTEGER,
     tibDeviceIdentity
        OBJECT IDENTIFIER,
     tibControlMode
        INTEGER
  }
tibDeviceAddress OBJECT-TYPE
  SYNTAX INTEGER (1..31)
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
     "Index into tibDevicesAddressedTable."
  ::= { tibDevicesAddressedEntry 1 }
tibDeviceIdentity OBJECT-TYPE
  SYNTAX OBJECT IDENTIFIER
  ACCESS read-only
  STATUS mandatory
  DESCRIPTION
     "Device identification. root OID for MIB that this device supports.
        For Power Supply use psIdent from SCTE-HMS-ROOTS (1.3.6.1.4.1.5591.1.4)
        For Fiber Node use fnIdent from SCTE-HMS-ROOTS (1.3.6.1.4.1.5591.1.5)
        For Generator use genIdent from SCTE-HMS-ROOTS (1.3.6.1.4.1.5591.1.6)"
  ::= { tibDevicesAddressedEntry 2 }
tibControlMode OBJECT-TYPE
  SYNTAX INTEGER { remote(1), local(2), notCommunicating(3) }
  ACCESS read-only
  STATUS optional
  DESCRIPTION
     "Control mode for this device
         1 = Remote device will respond to commands from master NE
         2 = Local device is under local control and will not respond
               to commands from master NE
```

```
3 = This device is not responding.
```

This item requires entries in the discrete property table"

```
::= { tibDevicesAddressedEntry 3 }
```

END